

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 161 109 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

05.12.2001 Bulletin 2001/49

(51) Int Cl.7: **H04Q 7/32**

(21) Application number: 01113318.8

(22) Date of filing: 31.05.2001

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

Designated Extension States:

AL LT LV MK RO SI

(72) Inventor: **Kim, Hoe-Won**

Suwon-city, Kyungki-do (KR)

(74) Representative: **Grünecker, Kinkeldey,**

Stockmair & Schwanhäusser Anwaltssozietät

Maximilianstrasse 58

80538 München (DE)

(30) Priority: 31.05.2000 KR 2000029543

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**

Suwon-City, Kyungki-do (KR)

(54) **Method of transmitting and receiving graphic short message service messages in a portable radio terminal**

(57) A method of transmitting and receiving image data by an SMS message is disclosed. To transmit a graphic SMS message, graphic SMS messages are registered, a portable radio terminal is changed over to

a graphic SMS message selection mode upon receipt of an SMS message editing key signal, a graphic SMS message is selected among the registered graphic SMS messages, and the image data of the selected graphic SMS message is edited and transmitted.




FIG. 2

Description

[0001] The present invention relates generally to a portable radio terminal system, and in particular, to a method of transmitting and receiving image data by a short message service (SMS) message.

[0002] In general, an SMS as well as a call service are provided to a portable radio terminal. The SMS allows a caller to leave a message in a text message regardless of the state of a called portable radio terminal, even when the called terminal is busy, thereby increasing user convenience.

[0003] Since the SMS is limited to text messages, however, a user may feel inconvenienced when he would rather transmit image data, such as a map, than transmit it in a text message to indicate a geographical location.

[0004] It is, therefore, the object of the present invention to provide a method of transmitting and receiving image data by an SMS message in a portable radio terminal.

[0005] To achieve the above object, a method of transmitting and receiving image data by an SMS message is provided. In the graphic SMS message transmitting method of the present invention, graphic SMS messages are registered, a portable radio terminal is switched over to a graphic SMS message selection mode upon receipt of an SMS message editing key signal, a graphic SMS message is selected among the registered graphic SMS messages, and the image data of the selected graphic SMS message is edited and transmitted.

[0006] In the present graphic SMS message receiving method, the header of an SMS message is checked upon receipt of the SMS message, it is determined whether the SMS message is a single graphic SMS message, the sequence number of the graphic SMS message is detected if the SMS message is not a single graphic SMS message, the data of the graphic SMS message is decoded according to the sequence number, and upon receipt of another graphic SMS message successively, the above steps are repeated.

[0007] The above object, features and advantages of the present invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings in which:

FIG. 1 is a block diagram of a portable radio terminal to which the present invention is applied;
FIG. 2 illustrates an embodiment of an SMS message format according to the present invention;
FIG. 3 is a flowchart illustrating an embodiment of a graphic SMS message registering procedure according to the present invention;
FIG. 4 illustrates an example of an image edited according to an embodiment of the present invention;
FIGs. 5 and 6 are flowcharts illustrating an embodiment of a graphic SMS message transmitting pro-

cedure according to the present invention;

FIG. 7 is a flowchart illustrating another embodiment of the graphic SMS message transmitting procedure according to the present invention;

FIG. 8 is a flowchart illustrating an embodiment of a graphic SMS message editing procedure according to the present invention;

FIG. 9 is a detailed flowchart illustrating the transmission operation shown in FIG. 6; and

FIG. 10 is a flowchart illustrating an embodiment of a graphic SMS message receiving procedure according to the present invention.

[0008] Preferred embodiments of the present invention will be described hereinbelow with reference to the accompanying drawings. In the following description, well-known functions or constructions are not described in detail since they would obscure the invention in unnecessary detail.

[0009] FIG. 1 is a block diagram of a portable radio terminal to which the present invention is applied. Referring to FIG. 1, a controller 111 provides overall control to the portable radio terminal. A memory 113 stores a control program and control data generated during the control operation of the controller 111.

[0010] A keypad 115 has a plurality of dialing digit keys and function keys such as MENU, SEND, and END, for generating a key signal corresponding to a key selected by a user and feeding the key signal to the controller 111.

[0011] A voice memory 117 stores a plurality of voice messages. A voice processor 119 processes a voice message read from the voice memory 117 to an analog voice signal and outputs the analog voice signal via a speaker. The voice processor 119 also processes an analog voice signal received from the user via a microphone to a digital signal.

[0012] A transmitter 121 modulates a signal received from the controller 111 to a digital radio signal and transmits the modulated signal to a duplexer 123. The duplexer 123 transmits the radio signal received from the transmitter 121 via an antenna and a signal received from the antenna to a receiver 125. The receiver 125 demodulates the radio signal received from the duplexer 123 and the controller 111 controls the call according to the demodulated signal received from the receiver 125.

[0013] A display 127 includes an LCD (Liquid Crystal Display) and an LED (Light Emitting Diode) and displays control data and input data under the control of the controller 111.

[0014] FIG. 2 illustrates an embodiment of an SMS message format according to the present invention. An SMS supports a fixed amount of text data in a typical portable radio terminal. For example, the European GSM (Global System for Mobile Communications) supports only 160 text characters. According to the present invention, due to the fixed SMS standard, an SMS message is identified as text data or image data according

to DOCUMENT TYPE 210 in its header. DOCUMENT TYPE 210 is a one-byte flag that discriminates between text data and image data according to its pattern.

[0015] OBJECT LIST 220 following DOCUMENT TYPE 210 is divided into OBJECT TYPE 230 and BODY 240, and includes real SMS data. OBJECT TYPE 230 indicates what the SMS data represents among a line, a curved line, a polygon, and text. BODY 240 provides the coordinates list of image data if OBJECT TYPE 230 indicates image data and provides text data if OBJECT TYPE 230 indicates text data.

[0016] FIG. 3 is a flowchart illustrating an embodiment of a graphic SMS message registering procedure according to the present invention and FIG. 4 illustrates an example of an image edited according to an embodiment of the present invention.

[0017] Referring to FIG. 3, upon receipt of a key signal from the keypad 115, the controller 111 determines whether the key signal was generated from a graphic SMS message registration key in step 311. If the key signal was generated from any other key, the controller 111 performs a normal operation with respect to the received key signal in step 313.

[0018] In the case of the graphic SMS message registration key, the controller 111 changes over the portable radio terminal to a graphic SMS message registration mode in step 315 and edits a graphic SMS message based on key signals received from the keypad 115 in step 317. The graphic SMS message may be edited in many ways. For example, a specific key may be set using a plurality of keys in combination in the keypad 115 and used as a kind of pointer to form a line by connecting a start point to an end point.

[0019] The editing step 317 will be described referring to FIG. 4.

[0020] If a user wants to send image data 410, a graphic SMS message 420 is edited using a plurality of straight lines 1-2, 2-3, 4-5, 5-6, 7-8, 8-9, 10-11, 11-12, 13-14, and 13-15 in the portable radio terminal. Here, straight line editing is performed by Huffman coding. A total of 20 bytes are assigned to the 10 straight lines, 2 bytes given to each straight line. 1 byte is assigned to each character and thus 6 bytes to the word "office". 1 byte is assigned to the header DOCUMENT TYPE 210.

[0021] A straight line is edited by connecting a start point to an end point using a specific key, for example, using a scroll key as a pointer in a graphic data editing mode. The start point and the end point each are presented in coordinates and the coordinates list is transmitted as real data in the graphic SMS message.

[0022] Upon receipt of a signal corresponding to the key END from the keypad 115, the controller 111 determines that the editing has been completed in step 319 and checks whether a storage key signal has been received from the keypad 115 in step 321. If the storage key signal was not received, the controller 111 checks whether a predetermined time (e.g., 5 seconds) has elapsed in step 323. If the predetermined time does not

expire, the controller 111 returns to step 321. After the predetermined time, the controller 111 ends the procedure.

[0023] Upon receipt of the storage key signal in step 321, the controller 111 stores the edited graphic SMS message in the memory 113 in step 325 and releases the graphic SMS message registration mode in step 327. If a plurality of graphic SMS messages are edited and registered, they are given sequence numbers, for identification. Then, the procedure ends.

[0024] FIGs. 5 and 6 are flowcharts illustrating an embodiment of a graphic SMS message transmitting procedure according to the present invention. Referring to FIGs. 5 and 6, the controller 111 checks whether an SMS message editing key signal has been received in step 511. If the SMS message editing key signal was not received, the controller 111 performs a normal operation with respect to the key signal in step 513.

[0025] Upon receipt of the SMS message editing key signal in step 511, the controller 111 reads a message prompting a user to choose an SMS message type between a graphic SMS message and a text SMS message from the memory 113 and displays the read message on the display 127 in step 515. The message may be given as a text message such as "select SMS message type" or as an icon image representing a key set by combining a plurality of keys in the keypad 115.

[0026] If a graphic SMS message selection key signal is received in step 517, the controller 111 changes over the portable radio terminal to a graphic SMS message selection mode in step 525. In the graphic SMS message selection mode, a graphic SMS message is selected among those registered in the memory 113. In step 527, the controller 111 reads a graphic selection message, for example, "enter selected number" from the memory 113 and displays the graphic selection message as an icon image on the display 127. The controller 111 checks whether a selection key signal has been received from the keypad 115 in step 529. If the selection key signal was not received, the controller 111 determines whether a predetermined time (e.g., 5 seconds) has elapsed in step 531. If the predetermined time has elapsed, the controller 111 regards the process that has been done so far as an error and performs a related operation in step 533.

[0027] Upon receipt of the selection key signal in step 529, the controller 111 reads a graphic SMS message with a sequence number corresponding to the selection key signal from the memory 113 in step 535 and checks whether the data amount of the selected graphic SMS message exceeds the SMS message standard, that is, the maximum data amount of a single text SMS message allowed for one transmission in step 537. If the graphic SMS message exceeds the SMS message standard, the controller 111 divides the graphic SMS message into a plurality of segments according to the SMS message standard in step 539. In this case, each graphic SMS message segment is formatted into a

graphic SMS message with DOCUMENT TYPE 210 indicating its segmentation from the original graphic SMS message and its sequence number in the original SMS message.

[0028] In step 611, the controller 111 encodes each graphic SMS message segment, for example, by Huffman coding. The controller 111 reads a transmission confirm message asking whether the graphic SMS message will be transmitted, for example, "Send?" from the memory 113 and displays it on the display 127 in step 613. In step 615, the controller 111 checks whether a SEND key signal has been received from the keypad 115. If the SEND key signal was not received, the controller 111 determines whether a predetermined time, say, 5 seconds has elapsed in step 617. If the predetermined time does not expire, the controller 111 returns to step 615. If the predetermined time expires, the controller 111 ends the procedure.

[0029] On the other hand, if the SEND key signal was received from the keypad 115 in step 615, the controller 111 sends the graphic SMS message in step 619 and checks whether the transmission is completed in step 621. If the transmission is completed, the controller 111 reads a transmission completion message, for example, "Completed" from the memory 113 and displays it on the display 127 in step 623.

[0030] FIG. 7 is a flowchart illustrating another embodiment of the graphic SMS message transmitting procedure according to the present invention. Referring to FIG. 7, the controller 111 checks whether an SMS message editing key signal has been received in step 711. If the SMS message editing key signal was not received, the controller 111 performs a normal operation with respect to the key signal in step 713.

[0031] Upon receipt of the SMS message editing key signal in step 711, the controller 111 reads a message prompting the user to choose an SMS message type between a graphic SMS message and a text SMS message from the memory 113 and displays the message on the display 127 in step 715. The message may be displayed as a text message such as "select SMS message type" or as an icon image representing a key set by combining a plurality of keys in the keypad 115.

[0032] If a graphic SMS message selection key signal is not received in step 717, the controller 111 checks whether a text SMS message selection key signal is received in step 719. If the text SMS message selection key signal is not received in step 719, the controller 111 regards the process that has been done so far as an error and performs a related operation in step 721. Upon receipt of the text SMS message selection key signal in step 719, the controller 111 performs a normal text SMS message editing and transmission operation in step 723.

[0033] Upon receipt of the graphic SMS message selection key signal in step 717, the controller 111 changes over the portable radio terminal to a graphic SMS message editing mode in step 725. In step 727, the controller

111 edits a user-selected graphic SMS message received from the keypad 115. The graphic SMS message may be edited in many ways. For example, a specific key is set using a plurality of keys in combination in the keypad 115 and used as a kind of pointer to form a line by connecting a start point to an end point. Or upon receipt of a specific key, selectable patterns are read from the memory 113 and displayed on the display 127, so that the user selects one of them. Upon receipt of an editing completion signal in step 729, the controller 111 temporarily stores the edited graphic SMS message in the memory 113 in step 731 and checks whether the edited graphic SMS message exceeds the SMS message standard, that is, the maximum data amount of a single text SMS message allowed for one transmission in step 733. If the graphic SMS message exceeds the SMS message standard, the controller 111 divides the graphic SMS message into a plurality of segments according to the SMS message standard in step 735 and goes to step 611 of FIG. 6.

[0034] FIG. 8 is a flowchart illustrating an embodiment of a graphic SMS message editing procedure according to the present invention. Referring to FIG. 8, after the controller 111 changes over the portable mobile terminal to an SMS message editing mode in step 811, it checks whether a pattern selection key signal has been received in step 813. If the pattern selection key signal was not received, the controller 111 checks whether a pattern editing key signal has been received in step 815. If the pattern editing key signal was not received, the controller 111 regards the process that has been performed so far as an error and performs a related operation in step 817.

[0035] Upon receipt of the pattern editing key signal in step 815, the controller 111 edits a pattern using a specific key in the keypad 115 as a pointer in the manner described in context with step 317 of FIG. 3 in step 819.

[0036] Upon receipt of the pattern selection key signal in step 813, the controller 111 reads selectable patterns from the memory 113 and displays them on the display 127 in step 821. The selectable patterns were registered in advance in the memory 113, such as a rectangle, a triangle, and so on.

[0037] In step 823, the controller 111 checks whether a selection key signal has been received from the keypad 115. Upon receipt of the selection key signal, the controller 111 displays a pattern corresponding to the selection key signal on the display 127 in step 825.

[0038] FIG. 9 is a flowchart illustrating the procedure of transmitting graphic SMS message segments shown in FIG. 6 in detail. Here, it is assumed that a graphic SMS message is divided into two segments.

[0039] Referring to FIG. 9, upon receipt of a SEND key signal from the keypad 115, the controller 111 transmits a first graphic SMS message in step 913 and checks whether the transmission is successful in step 915. If the transmission has failed, the controller 111 temporarily stores the failed first graphic SMS message

in the memory 113 in step 917. Then, the controller 111 reads a transmission failure message such as "Failed" from the memory 113 and displays it on the display 127 in step 919. If, at step 915 transmission was successful, the process proceeds to step 921.

[0040] In step 921, the controller 111 transmits a second graphic SMS message. The controller 111 checks whether the transmission is successful in step 923. If the transmission has failed, the controller 111 temporarily stores the failed second graphic SMS message in the memory 113 in step 925. Then, the controller 111 reads a transmission failure message such as "Failed" from the memory 113 and displays it on the display 127 in step 927.

[0041] On the other hand, if the second graphic SMS message was successfully transmitted in step 923, the controller 111 reads a transmission success message such as "Successful" from the memory 113 and displays it on the display 127 in step 931. In step 929, the controller 111 reads the failed first graphic SMS message from the memory 113 and retransmits it.

[0042] FIG. 10 is a flowchart illustrating an embodiment of a graphic SMS message receiving procedure according to the present invention. Referring to FIG. 10, upon receipt of an SMS message in step 951, the controller 111 detects the header DOCUMENT TYPE of the received SMS message in step 953 and checks whether the SMS message is a graphic SMS message based on DOCUMENT TYPE in step 955. If the SMS message is not a graphic SMS message, the controller 111 performs a normal text SMS message process in step 957.

[0043] In the case of a graphic SMS message, the controller 111 determines whether the graphic SMS message is a single one based on DOCUMENT TYPE in step 959. If the graphic SMS message is a single one, the controller 111 decodes the received image data in step 961 and notifies the user of receipt of the graphic SMS message by displaying it in the form of an icon image on the display 127 or sounding an alarm in step 963.

[0044] If the graphic SMS message is not a single one, the controller 111 detects a message sequence number from DOCUMENT TYPE in step 965. The controller 111 decodes the graphic SMS message according to its message sequence number in step 967 and checks whether another graphic SMS message has been received successively in step 969. Upon successive receipt of the next graphic SMS message, the controller 111 returns to step 965. If another graphic SMS message is not received successively, the controller 111 notifies the user of receipt of the graphic SMS message in step 971.

[0045] In accordance with the present invention as described above, a graphic SMS message as well as a text SMS message can be transmitted by an SMS in a portable radio terminal. Therefore, a user message is transmitted more effectively and more conveniently.

[0046] Furthermore, a graphic SMS message can be transmitted utilizing a conventional SMS simply by mod-

ifying the MMI (Man Machine Interface) of the portable radio terminal. Consequently, the use efficiency of radio resources in a mobile communication system is increased.

Claims

1. A method of transmitting a graphic Short Message Service (SMS) message in a portable radio terminal, comprising the steps of:

registering graphic SMS messages for transmission;
switching the portable radio terminal to a graphic SMS message selection mode upon receipt of an SMS message by inputted key signal;
being selected as transmitting graphic SMS message among the registered graphic SMS messages;
encoding image data of the selected graphic SMS message; and
transmitting the encoded image data.

2. The method of claim 1, wherein the step of registration comprises the steps of:

switching the portable radio terminal mode to a graphic SMS message registration mode upon receipt of a graphic SMS registration key signal;
editing the graphic SMS message using a pointer in the graphic SMS message registration mode; and
registering the edited graphic SMS message upon receipt of a storage key signal.

3. The method of claim 1, wherein the graphic SMS message includes:

a header indicating whether an SMS message is a text type or an image data type;
a first field indicating whether the SMS message is presented as a straight line, a curved line, a polygon, or a text; and
a second field that provides a coordinates list of image data if the SMS message is the image data type and provides text data if the SMS message is the text type.

4. The method of claim 1, wherein the image data is encoded by Huffman coding.

5. A method of transmitting a graphic short message service (SMS) message in a portable radio terminal, comprising the steps of:

prompting a user to choose an SMS message type between a graphic SMS message and a

- text SMS message upon receipt of an SMS message editing key signal;
switching the portable radio terminal mode to a graphic SMS message editing mode if the graphic SMS message is selected as the SMS message type to be transmitted;
editing the graphic SMS message to be transmitted in the graphic SMS message editing mode;
encoding the edited graphic SMS message if the editing is completed; and
transmitting the encoded graphic SMS message.
6. The method of claim 5, further comprising the steps of editing a text SMS message to be transmitted and transmitting the edited text SMS message if the text SMS message is selected as the SMS message type to be transmitted.
7. The method of claim 5, wherein a specific key is set using a plurality of keys of the portable radio terminal in combination and a line is formed by connecting a start point to an end point using the specific key as a pointer in the graphic SMS message editing step.
8. The method of claim 5, wherein the graphic SMS message editing step comprises:
displaying pre-registered selectable patterns upon receipt of a pattern selection key signal;
selecting one of the selectable patterns; and
displaying the selected pattern.
9. The method of claim 5, wherein the graphic SMS message includes:
a header indicating whether an SMS message is a text type or an image data type;
a first field indicating whether the SMS message is presented as a straight line, a curved line, a polygon, or a text; and
a second field that provides a coordinates list of image data if the SMS message is the image data type and provides text data if the SMS message is the text type.
10. The method of claim 5, wherein the image data is encoded by Huffman coding.
11. The method of claim 5, further comprising the steps of:
determining whether a data amount of the edited graphic SMS message exceeds an SMS message standard length;
stored with dividing the graphic SMS message into a plurality of segments according to the SMS message standard length if the data amount of the edited graphic SMS message exceeds the SMS message standard length;
encoding the graphic SMS message segments; and
sequentially transmitting the encoded graphic SMS message segments.
12. The method of claim 11, wherein the sequential transmission step comprises:
sequentially transmitting the graphic SMS message segments in an order of a higher priority in the sequence numbers, which the headers of SMS message segments reveal;
completing the sequential transmission procedure if a transmission-failed graphic SMS message segment exists; and
retransmitting the transmission-failed graphic SMS message segment.
13. The method of claim 11, wherein a specific key is set using a plurality of keys of the portable radio terminal in combination and a line is formed by connecting a start point to an end point using the specific key as a pointer in the graphic SMS message editing step.
14. A method of receiving a graphic short message service (SMS) message in a portable radio terminal, comprising the steps of:
1) checking a header of an SMS message upon receipt of the SMS message;
2) determining whether the SMS message is a single graphic SMS message;
3) detecting a sequence number of the graphic SMS message if the SMS message is not a single graphic SMS message;
4) decoding data of the graphic SMS message according to the sequence number; and
5) returning to step 3) upon receipt of a successive graphic SMS message after step (4).
15. The method of claim 14, further comprising the step of processing a text SMS message if the received SMS message is the text SMS message by checking the header of the SMS message.
16. The method of claim 14, further comprising the steps of:
decoding the data of the graphic SMS message if the received SMS message is a single graphic SMS message; and
providing notification that the graphic SMS message has been received.

17. A method of transmitting a graphic short message service (SMS) message in a portable radio terminal, comprising the steps of:

switching the portable radio terminal to a graphic SMS message editing mode upon determining the request of transmission of the graphic SMS message; 5
editing the graphic SMS message to be transmitted in the graphic SMS message editing mode; and 10
dividing the edited graphic SMS message into a plurality of segments to an SMS message standard length if a data amount of the edited graphic SMS message exceeds an SMS message standard length. 15

18. The method of claim 17, wherein pre-registered image data is selected or image data is received using a pointer in the graphic SMS message editing step. 20

25

30

35


40

45

50

55

FIG. 1






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 161 109 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
26.11.2003 Bulletin 2003/48

(51) Int Cl.7: **H04Q 7/32**

(43) Date of publication A2:
05.12.2001 Bulletin 2001/49

(21) Application number: **01113318.8**

(22) Date of filing: **31.05.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Kim, Hoe-Won**
Suwon-city, Kyungki-do (KR)

(74) Representative: **Grünecker, Kinkeldey,
Stockmalr & Schwanhäusser Anwaltssozletät
Maximilianstrasse 58
80538 München (DE)**

(30) Priority: **31.05.2000 KR 2000029543**

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**
Suwon-City, Kyungki-do (KR)

(54) **Method of transmitting and receiving graphic short message service messages in a portable radio terminal**

(57) A method of transmitting and receiving image data by an SMS message is disclosed. To transmit a graphic SMS message, graphic SMS messages are registered, a portable radio terminal is changed over to

a graphic SMS message selection mode upon receipt of an SMS message editing key signal, a graphic SMS message is selected among the registered graphic SMS messages, and the image data of the selected graphic SMS message is edited and transmitted.




FIG. 2

EP 1 161 109 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 11 3318

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 97 32439 A (DECKER PETER ; KAARTINEN KALEVI (DE); GUSTAFSSON PATRIK (FI); NOKIA) 4 September 1997 (1997-09-04) * page 1, line 35-37 * * page 3, line 17 - page 4, line 26 * * page 7, line 19-38 * ---	1-18	H04Q7/32
X	"UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEMS (UMTS) TECHNICAL REALIZATION OF THE SHORT MESSAGE SERVICE (SMS) (3G TS 23.040 VERSION 3.4.1 RELEASE 1999)" ETSI TS 123 040 V3.4.1. April 2000 (2000-04), pages 1-127, XP002256298	1.3-6, 9-12, 14-18	
Y	* paragraphs [3.10.2], [9.2.3.24], [9.2.3.24.1] * ---	2,7,8,13	
Y	GB 2 308 523 A (NORTHERN TELECOM LTD) 25 June 1997 (1997-06-25) * page 2, line 14-31 * * page 6, line 18 - page 7, line 2 * * figure 3 * -----	2,7,8,13	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04Q
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 1 October 2003	Examiner Weinmiller, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1501 03/92 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 11 3318

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-10-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9732439	A	04-09-1997	FI 960895 A	27-08-1997
			AU 723988 B2	07-09-2000
			AU 1881497 A	16-09-1997
			AU 4733599 A	11-11-1999
			BR 9707868 A	27-07-1999
			CA 2247449 A1	04-09-1997
			CA 2365050 A1	04-09-1997
			CA 2365116 A1	04-09-1997
			CA 2365167 A1	04-09-1997
			CA 2365588 A1	04-09-1997
			CN 1412991 A	23-04-2003
			CN 1413044 A	23-04-2003
			CN 1413045 A	23-04-2003
			CN 1413046 A	23-04-2003
			CN 1212109 A	24-03-1999
			EP 1271336 A2	02-01-2003
			EP 1271337 A2	02-01-2003
			EP 1276338 A2	15-01-2003
			EP 1280367 A2	29-01-2003
			EP 0882375 A2	09-12-1998
			WO 9732439 A2	04-09-1997
			JP 2000505621 T	09-05-2000
			US 6370389 B1	09-04-2002
			US 6400958 B1	04-06-2002
			US 6292668 B1	18-09-2001
			US 6188909 B1	13-02-2001
GB 2308523	A	25-06-1997	AU 1163497 A	17-07-1997
			WO 9723992 A1	03-07-1997